



CYS Model Technology Co.,LTD
Add: No.290,Changma Road.Changping Town.Dongguan,Guangdong. CHINA
Tel: +86 769 81091556 Fax:+86 769 81091557
Email: info@cysmodel.com

Specification Sheet

Item No.	CYS-S3120
Type	Digital
Weight	20g
Size	23*12*29.1mm
Control System	(+)Pulse Width Control 1500usec Neutral
Required Pulse	
Operating Voltage	6.0 ~7.4Volts
Operating Temperature Range	(-)20 to +60 degree C
Operating Speed (6.0V)	0.075sec/60° at no load
Operating Speed (7.4V)	0.06sec/60° at no load
Stall Torque (6.0V)	3.0kg.cm
Stall Torque (7.4V)	4.0kg.cm
Operating Angle	45deg.one side pulse traveling 500 usec
360 Modifiable	No
Direction	Anticlockwise/Pulse Traveling 1000~2000usec
Current Drain (6.0V)	20mA/idle and 50mA no load operating
Current Drain (7.4V)	20mA/idle and 55mA no load operating
Stall Current	1.5A/1.8A
Dead Band Width	4usec
Motor Type	coreless motor
Bearing Type	Dual Ball Bearing
Horn gear spline	21T
Gear Type	Metal
Connector Wire Length	180mm
Wire info	Brown/Black = Negative
	Red = Positive
	Orange/White = Signal